

Shell Solar

Shell PowerMax™ solar modules for off-grid markets

1st edition 2005

General

Shell PowerMax™ is a range of high performance solar products – with designs created specifically for off-grid applications.

The Shell PowerMax™ Plus 25 product contains 36 series connected 125mm x 41.5mm multi-crystalline silicon solar cells, which can generate a peak power of 25 watts at 17 volts.

Qualifications and Certificates

The Shell PowerMax™ Plus 25 solar module meets the following requirement:

IEC61215 Ed. 1



Limited Warranties*

- Peak Power for 10 years (category B)
- 2 year workmanship warranty

* See Shell Solar Limited Warranty for PV-Modules

Shell PowerMax™ Plus 25



**ELECTRICAL EQUIPMENT,
CHECK WITH YOUR INSTALLER**

Due to continuous research and product improvement, the specifications in this Product Brochure are subject to change without notice. Specifications can vary slightly. For installation and operation instructions, please see the applicable manuals. No rights can be derived from this Product Brochure and Shell Solar assumes no liability whatsoever connected to or resulting from the use of any information contained herein.

References in this Product Brochure to 'Shell Solar' are to companies and other organizational entities within the Royal Dutch/Shell Group of Companies that are engaged in the photovoltaic solar energy business. Shell Solar has its principal office in Amsterdam, The Netherlands.

The Shell PowerMax™ advantage

Exceptional Performance

- High efficiency crystalline silicon cell technology; enhanced by TOPS and new silicon nitride anti-reflection coatings.
- One of the industry's leading energy yields in a wide variety of climates.
- Products rated on fully stabilized initial power so you get the power you pay for.

Proven Reliability

- Module design proven over 30 years of field operations with reliability in excess of 99.9%.
- Extended limited power warranties backed by a company you can trust.
- IEC 61215 certification.

Easy to Install


- Field-accessible junction box.
- 4 mounting holes per product; 2 grounding holes.



Shell PowerMax™ Plus 25 Photovoltaic Solar Module

Mechanical Specifications

A torsion and corrosion-resistant anodised aluminium frame ensures dependable performance, even under harsh weather conditions. Pre-drilled mounting holes are provided for ease of installation.



Outside dimensions (mm)	550 x 449
Thickness (mm)	38
Weight (kg)	3.4

For installation instructions, please refer to the Shell Solar Installation and Safety Instructions.

Electrical Characteristics

Data at Standard Test Conditions (STC)

STC: irradiance level 1000W/m², spectrum AM 1.5 and cell temperature 25°C.

Rated power	P_r	25W
Peak power*	P_{mpp}^{**}	25W
Maximum system voltage	V_{sys}	120V
Peak power voltage	V_{mpp}	17.0V
Peak power current	I_{mpp}	1.47A
Open circuit voltage	V_{oc}	21.5V
Short circuit current	I_{sc}	1.63A
Minimum peak power	$P_{mpp\ min}$	22.5W
*Tolerance on Peak Power		+/-10%

** The abbreviation "mpp" stands for Maximum Power Point

Typical Data at Nominal Operating Cell Temperature (NOCT) conditions

NOCT: irradiance level 800W/m², spectrum AM 1.5, wind velocity 1 m/s, T_{amb} 20°C.

Temperature	T_{NOCT}	44 °C
Mpp power	P_{mpp}	19 W
Mpp voltage	V_{mpp}	15.6 V
Open circuit voltage	V_{oc}	19.6 V
Short circuit current	I_{sc}	1.40 A

Typical data at low irradiance

The relative reduction of module efficiency at an irradiance of 200W/m² in relation to 1000W/m² both at 25°C cell temperature and AM 1.5 spectrum is 8%.

Temperature coefficients

αP_{mpp}	-0.50 %/°C
αV_{mpp}	-76 mV/°C
αI_{sc}	0.48 mA/°C
αV_{oc}	-74mV/°C

Maximum system voltage: 120 Vdc

For further information on all Shell Solar products contact:

Shell Solar GmbH
Domagkstr. 34
80807 Munich
Germany
solarinfo@shell.com
www.shell.com/solar

V1/PowerMax/Off-Grid 12V/25/Int/04/05

